


ALPHA AL32

High precision automatic level









Stability



brake screw







IP54

ALPHA AL32-Automatic level

The ALPHA AL32 automatic level can be used for 3rd or 4th order leveling, building constructions and normal leveling surveying applications.


- The automatic compensator, which adopts crossed suspension tapes and air damper, greatly improves the work efficiency and leveling accuracy.
- The ALPHA AL32 is also equipped with a press button for compensator checking.
- The metal body design provides better protection.

Functional Features >>>



Application Scenario >>>





Specification	
Telescope Magnification	32X
Standard Deviation for 1km Double-run Leve	ling 1.0mm
Setting Accuracy	±0.3"
Compensator Working Range	±15'
Telescope Image	Erect
Effective Aperture Size of Objective	40mm
Angle of FOV	1°17.5′
Shortest Sighting Distance	0.5m
Stadia Multiplication / Addition Constants	100/0
Accuracy of Circular Level	8′/2mm
Graduation Value	360°or 400gon
Degrees of Protection	IP54
Compensator Type	X wire-hung and air-damping
Instrument Size	229mm x 145mmx175mm
Net Weight	1.8Kg



- +8618565149475
- (http://www.alphageo-info.com
- alphageoinfo@gmail.com
- Building C, Runhui Science and Technology Park, Shenzhou Road, Huangpu District, Guangzhou 510663, Guangdong, China

